

S E R I E S



59HA Aluminium

ROTARY INCREMENTAL SHAFT ENCODER

The 59HA Series (59mm diameter frame size encoder) is a precision, versatile through hollow shaft encoder rated at IP67 and boasts a total frame depth of only 53mm from front to back. Its extended universal radius mounting plate makes it ideal for mounting directly onto many types of motor. Its advanced technology allows this encoder to be offered in 'any' resolution from 1ppr up to 65536ppr.



S P E C I F I C A T I O N S

Body:
Aluminium

Cover:
Aluminium

Shaft:
Stainless Steel

Bearings
Ballraces

Shaft Sealing:
Front: Shaft Seal
Rear: Shaft seal

Protection:
IP67

Operating Temp:
-40 to +100°C

Maximum Speed:
6000 RPM

Torque:
4Ncm (typical)

Starting Torque:
0.025Nm (max)

Shaft Loading:
Designed to support its own weight

Cable:
Screened, oil and water proof

Impulse Frequency:
300KHz @ 5v output
160KHz @ 24v output

Supply Voltage:
5 to 30vdc

S T A N D A R D R E S O L U T I O N S

1,2,3,4,5,6,7,8,9,10,11,12,13,14,15,16,17,18,19,20,21,22,23,24,25,26,27,28,29,30,31,32,33,34,35,36,37,38,39,40,41,42,43,44,45,46,47,48,49,50,51,52,53,54,55,56,57,58,59,60,61,62,63,64,65,66,67,68,69,70,71,72,73,74,75,76,77,78,79,80,81,82,83,84,85,86,87,88,89,90,91,92,93,94,95,96,97,98,99,100,101,102,103,104,105,106,107,108,109,110,111,112,113,114,115,116,117,118,119,120,121,122,123,124,125,126,127,128,129,130,131,132,133,134,135,136,137,138,139,140,141,142,143,144,145,146,147,148,149,150,151,152,153,154,155,156,158,159,160,161,162,163,164,165,166,167,168,169,170,171,172,173,174,175,176,177,178,179,180,181,182,183,184,185,186,187,188,189,190,191,192,193,194,195,196,197,198,199,200,201,202,203,204,205,206,207,208,209,210,211,212,213,214,215,216,217,218,219,220,221,222,223,224,225,226,227,228,229,230,231,232,233,234,235,236,237,238,239,240,241,242,243,244,245,246,247,248,249,250,251,252,253,254,255,256,257,258,259,260,261,262,263,264,265,266,267,268,269,270,271,272,273,274,275,276,277,278,279,280,281,282,283,284,285,286,287,288,289,290,291,292,293,294,295,296,297,298,299,300,301,302,303,304,305,306,307,308,309,310,311,312,313,314,315,316,317,318,319,320,321,322,323,324,325,326,327,328,329,330,331,332,333,334,335,336,337,338,339,340,341,342,343,344,345,346,347,348,349,350,351,352,353,354,355,356,357,358,359,360,361,362,363,364,365,366,367,368,369,370,371,372,373,374,375,376,377,378,379,380,381,382,383,384,385,386,387,388,389,390,391,392,393,394,395,396,397,398,399,940,941,942,943,944,945,946,947,948,949,950,951,952,953,954,955,956,957,958,959,960,961,962,963,964,965,966,967,968,969,970,971,972,973,974,975,976,977,978,979,980,981,982,983,984,985,986,987,988,989,990,991,992,993,994,995,996,997,998,999,1000,1001,1002,1003,1004,1005,1006,1007,1008,1009,1010,1011,1012,1013,1014,1015,1016,1017,1018,1019,1020,1021,1022,1023,1024,1025,1026,1250,1270,1400,1500,1800,2000,2048,2250,2400,2500,3000,3600,4000,4096,5000,6000,9000,10000...



CONNECTIONS

FUNCTION CABLE

0 Volts	White
+ Volts	Brown
A Channel	Green
B Channel	Grey
Z Channel	Blue
A/ Channel	Yellow
B/ Channel	Pink
Z/ Channel	Red

ACCESSORIES AVAILABLE

~ OTHER MOUNTING BRACKETS

STANDARD FEATURES

- IP67 Protection
- 1 PPR through to 65536 PPR available
- Short - Circuit & Overload Protection
- High Noise Immunity
- Robust Construction
- Fast Delivery

STANDARD ORDERING CODES

